

**Informações do Produto**

Reference No.: DMSL-CL10W013
DMSL-CL14W014 | DMSL-CL20W015

Power: 10W, 14W, 20W

Light Output: 700 lm / 980 lm / 1400 lm

Rated Voltage: AC220-240V

Color Temperature (CCT): 2700K / 3000K / 4000K / 6000K

Beam Angle: 20° / 40° / 60°

CRI: >90Ra

IP: 65

Color Finish: White / Black (other colors upon request)

Material: Aluminum

Certifications: CE & RoHS

**Product Description**

With a modern and minimalist design, this recessed LED ceiling fixture offers high water resistance and uniform, efficient illumination.

Ideal for residential and commercial environments requiring durability, style, and energy efficiency.



*CE marking indicates that the product complies with European Union safety, health, and environmental standards, allowing it to be legally marketed within the European Economic Area.

Technical Drawing



Data Sheet

Reference No.	Dimensions (mm)	Power (W)	Luminous	Voltage	Color Temperature	CRI	IP Rating	Beam Angle
DMSL-CL10W013	D88*H62mm Cutout: D75mm	10	700LM	220-240V	2700K/ 3000K/ 4000K/ 6000K	>90Ra	65	20°/ 40°/ 60°
DMSL-CL14W014	D110 × H74 mm Cutout: D95mm	14	980LM					
DMSL-CL20W015	D142*H86mm Cutout: D125mm	20	1440LM					
Finish: White / Black Material: Aluminum Certifications: CE & RoHS								

Warranty Period: 3 years

IP: Indicates the level of protection of a device against dust and water.

CRI: Indicates how a light renders colors.

CCT: Indicates whether the light appears warmer (yellowish) or cooler (whiter/bluer), measured in Kelvin (K).



*CE marking indicates that the product complies with European Union safety, health, and environmental standards, allowing it to be legally marketed within the European Economic Area.